

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
1 B2B40-ZS	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 2.8~12mm varifocal lens, Max. IR LEDs Length 40m Support Smart IR, Micro SD card memory, IP67, PoE		27,000,000
2 B1B40P EZ-IP 2	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		18,260,000
3 B1B20P-L EZ-IP 2	1/2.7" 2Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@1080P(1920×1080) & 25/30fps@1.3MP(1280×960) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		12,980,000
4 T1B40P EZ-IP 2	1/3" 4Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		18,260,000
5 T1B20P-L EZ-IP 2	1/2.7" 2Megapixel progressive scan CMOS H.265+ & H.265 dual-stream encoding 20fps@1080P(1920×1080) & 25/30fps@1.3MP(1280×960) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC,HLC 3.6mm fixed lens, Max. IR LEDs Length 30m Support Smart IR, IP67, PoE		12,980,000
6 B1A30	1/3" 3Megapixel progressive scan CMOS H.264+/H.264 dual-stream encoding 20fps@3M(2048x1536)&25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Max. IR LEDs Length 30m, IP67, PoE		12,170,000
11 NVR1A04HS-4P	4 channel IP camera input, 1/4/8/9 channel Live Preview H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 Support 4PoE port, 100 Mbps Network Card, P2P support		17,850,000
12 NVR1A08HS	8 channel IP camera input, 1/4/8/9 channel Live Preview H.264+/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 6MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support		11,090,000

1	PSD81602-A360	<p>8x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Eight 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 2x25fps@4096x1800+50/60fps@1080P Support 360-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10</p>		Call
2	PSD8802-A180	<p>4x2MP Multi-Sensor Panoramic Network Camera+PTZ Camera Panoramic: Four 1/1.9" 2Megapixel progressive scan CMOS 5mm fixed lens PTZ: One 1/1.9" 2Megapixel progressive scan CMOS 5.5mm~206mm, 37x optical zoom H.265+/H.265/H.264+/H.264 triple-stream encoding 25fps@4096x1800+50/60fps@1080P Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Smart tracking, Intelligent Function(Tripwire, Intrusion) 2/1 channel Audio In/Out, 7/2 channel Alarm In/Out RS485, Micro SD memory, IP67, IK10</p>		Call
3	PFW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Bullet Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/2 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
4	PFW8601-A180	<p>3x2MP Multi-Sensor Panoramic Network IR Bullet Camera Three 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25fps@4096x832, 3.6mm fixed lens Support 180-degree panoramic view WDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call
5	PDBW8800-A180	<p>4x2MP Multi-Sensor Panoramic Network IR Dome Camera Four 1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Max 25fps@4096x1800, 3.0mm fixed lens Support 180-degree panoramic view DWDR, Day/Night(ICR), 3DNR, AWB, AGC, HLC, BLC Intelligent Function Tripwire, Intrusion, Object Abandoned/Missing, Heat Map, E-PTZ 1/1 channel Audio In/Out, 2/1 channel Alarm In/Out Max. IR LEDs length 30m, Micro SD memory, IP67, IK10,PoE+</p>		Call

دوربین ANPR با قابلیت تشخیص پلاک ،مناسب برای ورودی های پارکینگ


2 Megapixel Full HD WDR Access ANPR Camera

-Embedded with LPR algorithm inside the camera

-plate cutout, snapshot preview, recording

-White list database,1 ch relay out to control the barrier performance for outdoor applications-

6 ITC237-PW1B-IRZ



1/2.8" 2Megapixel progressive scan CMOS

H.265/H.264M/H.264H/H.264B dual-stream encoding

25/30fps@1080P(1920×1080), 2.7mm~12mm Motorize lens

WDR(140dB),BLC,HLC,Day/Night(ICR),3DNR,AWB,AGC,BLC

Mirco SD card 64GB, IR Distance 3~8m, IP67, IK10, PoE



121,720,000

7 IPC5831EP-ZE



1/2.5" 8 Megapixel progressive scan STARVIS™ CMOS

H.265+/H.265/H.264+/H.264 Triple-stream encoding

15fps@4K(3840×2160),25/30fps@3Mp(2304×1296)

2.7mm ~12mm motorized lens, Max. Aperture F1.6

WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC

Micro SD card memory , 128 GB

1/1 Audio In/Out, 2/1 Alarm In/Out

Max. IR LEDs Length 50m , Smart IR, IP67,IK10, PoE

(Tripwire|Intrusion|Object Abandoned/Missing|Face)

1/2.5" 8Megapixel progressive scan CMOS

H.265&H.265&H.264&MJPEG triple-stream encoding

15fps@4K(3840×2160),25/30fps@3Mp(2304×1296)

DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC

4mm & 2.8mm fixed lens, Max. IR LEDs Length 40m

Micro SD card memory , 128 GB, IP67, PoE

Smart Detection (Tripwire|Intrusion | Scene Change | Face)

8MP Lite IR Vari-focal Starlight Bullet Network Camera

1/2.7" progressive scan CMOS image sensor, low illuminance, high image definition

Smart H.265/H.264 codec, MJPEG, high compression rate, ultra-low bit rate

9 HFW2831T-ZS



8MP (3840 × 2160) @15 fps, 2688×1520 @25/30 fps

WDR(120db), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, Region of

Interest, Voltage Detection

2.7 mm~13.5 mm Motorized fixed lens

Max. IR LEDs Length 60m, Micro SD card memory , 256 GB

IP67, PoE, Smart Detection (Tripwire|Intrusion)

6MP WDR IR Bullet Network Camera

1/2.9" 6Megapixel progressive scan STARVIS™ CMOS

H.265&H.264 Triple-stream encoding

20fps@6M(3072×2048),25/30fps@4M(2688×1520)

WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC

7mm~35mm(5x zoom) Motorized lens

Max. IR LEDs Length 100m, Micro SD card memory , 128 GB

2/1 Alarm in/out, 1/1 audio in/out, IP67, IK10, PoE

(Tripwire|Intrusion | Object Abandoned | Missing| Face)

1/2.9" 6Megapixel progressive scan STARVISTM CMOS

H. 265+ & H.265 & H.264+ & H.264 triple-stream encoding

20fps@6MP(3072x2048), 25/30fps@4MP(2688x1520)

WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC

3.6mm fixed lens, Max. IR LEDs Length 40m

Micro SD card memory , 128 GB, IP67, PoE

(Tripwire|Intrusion |Object Abandoned/Missing| Face)

1/2.7" 5Megapixel progressive CMOS

2.7~13.5mm Motorized lens

15fps@5M(2592×1944)&25/30fps@3M(2304×1296)

H.265+/H.265/H.264+/H.264 dual-stream encoding

WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC

Mirco SD card 128GB, Max IR LEDs Length 60m ,Smart IR

IP67, PoE, Smart Detection (Tripwire|Intrusion)

12 HFW2531TP-ZS



11 HFW4631EP-SE

1/2.7" 5Megapixel progressive CMOS

15fps@5M(2592×1944)&25/30fps@3M(2304×1296)

H.265+/H.265/H.264+/H.264 dual-stream encoding

WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC

Mirco SD card 128GB, Max IR LEDs Length 60m ,Smart IR

IP67, PoE, Smart Detection (Tripwire|Intrusion)



60,000,000



89,000,000





44,000,000









50,000,000










13		<p>4MP Pro AI IR Vari-focal, 1/1.8" 4Megapixel progressive scan CMOS H.265,H.264,H.264B,H.264H, MJPEG triple-stream encoding Max 25/30fps@4Mp(2688x1520), 50/60fps@2Mp(1920 x 1080) WDR(140dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, EIS, Defog, Region of Interest, 8mm-32mm Motorized lens, Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 Smart Detection Tripwire, intrusion (Recognition of vehicle and people), Object Abandoned / Missing, fast moving, loitering detection, parking detection and people gathering Support Line crossing/Region/Queueing people counting; Support 4 accesses independent detection, 4 areas independent detection, Scene Change, Heatmap, IP67, IK10, PoE</p>		93,000,000
14		<p>4MP WDR IR Bullet Network Camera 1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding Max 25/30fps@4Mp(2688x1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, 2.7mm ~13.5mm motorized lens Max. IR LEDs Length 50m, Smart IR, Micro SD card memory , 128 GB Audio in/Out 1/1, Alarm In/Out 2/1 IP67, IK10, PoE, (Tripwire Intrusion Object Abandoned / Missing Face)</p>		75,000,000
15		<p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 triple-stream encoding 50/60fps@1080(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 5.3mm ~ 64mm 12x zoom lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card up to 128 GB, Max. IR LEDs Length 200m , Smart IR IP67, IK10, PoE, (Tripwire Intrusion Object Abandoned/Missing Face)</p>		77,000,000
16		<p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding 50/60fps@1080(1920x1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 13.5mm motorized lens 1/1 Audio in/Out, 2/1 Alarm In/Out Micro SD card memory , 128 GB, Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE, Smart Detection (Tripwire Intrusion Object Abandoned/Missing Face)</p>		72,000,000
17		<p>4MP WDR IR Bullet Network Camera 1/3" 4Megapixel progressive CMOS 2.7mm~13.5mm motorized lens 25/30fps@4Mp(2688x1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Facedetection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 2/1 Alarm in/out, 1/1 audio in/out Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, IK10, PoE</p>		65,000,000
18		<p>4MP WDR IR Mini Bullet Network Camera 1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 25/30fps@4Mp(2688x1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>		34,500,000





20	<p>HFW3441TP-ZS-27135</p> <p>Starlight Wiz Sense</p>	<p>4MP IR Vari-focal Bullet WizSense Network Camera 1/3"4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.5 2.7 mm-13.5 mm Motorized lens 25/30fps@4Mp(2688x1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Micro SD memory 256GB Max. IR LEDs Length 80m, Smart IR, IP67, IK10, PoE</p>		55,500,000
21	<p>HFW2431TP-ZS-S2</p> <p>Starlight</p>	<p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7-13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:60 m, Smart IR IP67, PoE</p>		45,000,000
22	<p>HFW1431SP-0360B-S4</p>	<p>4MP Entry IR Fixed-focal Bullet Network Camera 1/3"4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @25fps Min. Illumination:0.03 Lux@F2.0 3.6 Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR IP67, PoE</p>		22,000,000
23	<p>HFW1431SP</p> <p>Ambarella</p>	<p>1/3" 4Megapixel progressive CMOS 3.6mm fixed lens 20fps@4M(2688x1520) &25/30fps@3M(2304x1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, PoE</p>		27,500,000
24	<p>HFW4231EP-S</p> <p>Ambarella</p>	<p>1/2.8" 2Megapixel progressive scan STARVIS™ CMOS(Starlight) 3.6mm fixed lens 50/60fps@1080P(1920x1080) H.265+/H.265/H.264+/H.264 triple-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Smart Detection supported: Face Detection, Tripwire, Intrusion, Object Abandoned/Missing Max. IR LEDs Length 40m, Micro SD card 128GB, IP67, PoE</p>		36,000,000
25	<p>HFW2431SP-S-S2</p> <p>Starlight</p>	<p>4MP WDR IR Bullet Network Camera 1/3" 4MP image sensor SMART H.264/H.265 dual stream encoding 4MP (2688 x 1520)@20 fps,2560 x 1440 @25fps Min. Illumination:0.008 Lux@F1.6 3.6mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance: 30 m, Smart IR IP67, PoE</p>		25,200,000






26	<p>HFW2231SP-S-S2</p> <p>Starlight</p>	<p>2MP WDR IR Bullet Network Camera, starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 3.6mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, RoI Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE</p>		22,800,000
27	<p>HFW2230SP-S</p>	<p>2MP IR Bullet Network Camera 1/2.7" CMOS image sensor, low illuminance, high image definition H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 3.6mm, Max. IR LEDs Length 30m, Smart IR Micro SD card memory 128 GB IP67, PoE, AVI(Tripwire Intrusion)</p>		19,800,000
28	<p>HFW2231T-ZAS</p>	<p>2MP WDR IR Bullet Network Camera 1/2.8" 2Megapixel progressive Starvis™ CMOS H.265+/H.265/H.264+/H.264 Double-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI 2.7mm~13.5mm, Max. IR LEDs Length 60m, Smart IR Micro SD card memory , 128 GB, Audio I/O 1/1, Alarm I/O 1/1 IP67, IK10(Optional), PoE, (Tripwire Intrusion Scene Change)</p>		39,500,000
29	<p>HFW1231SP</p> <p>Starlight</p>	<p>1/2.8" 2Megapixel progressive CMOS, Starlight H.265&H.264 dual-stream encoding 25/30fps@1080P(1920×1080) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC 2.8mm fixed lens, Max. IR LEDs Length 30m, Smart IR IP67, PoE, Smart Detection (Tripwire Intrusion)</p>		21,700,000
30	<p>HFW1230SP-S4</p>	<p>2MP Entry IR Fixed-focal Bullet Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080p) @25/30 fps Min. Illumination:0.01 Lux@F2.0 3.6 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI max IR distance:30 m, Smart IR IP67, PoE</p>		17,500,000
31	<p>HFW1230SP-S2</p>	<p>1/2.7" 2Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 3.6mm fixed lens, Max. IR LEDs Length 30m, IP67, PoE</p>		18,000,000
32	<p>HDBW5831EP-ZE</p> <p></p>	<p>1/2.5" 8Megapixel progressive scan STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-stream encoding 15fps@4K(3840×2160),25/30fps@3M(2304×1296) WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~ 12mm motorized lens 1/1 Audio in/Out, 1/1 Alarm In/Out Micro SD card memory , 128 GB Max. IR LEDs Length 50m , Smart IR IP67, IK10, PoE+, (Tripwire Intrusion Object Abandoned/Missing Face)</p>		88,000,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
33 HDBW5431EP-Z-H	<p>1/3" 4Megapixel progressive scan CMOS H.265+/H.265/H.264+/H.264 & MJPEG triple-stream encoding Max 20fps@4Mp(2560×1440), 25/30fps@3M(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.7mm ~12mm motorized lens, Max. IR LEDs Length 50m IP67, IK10, PoE, Micro SD card memory , 128 GB Audio in/Out, Alarm In/Out Smart Detection (Tripwire Intrusion Scene Change Face)</p>		75,000,000
34 HDBW4831EP-ASE	<p>1/2.5" 4K progressive scan Starvis CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160), 25/30fps@3Mp(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 30m Alarm in/out, Audio in/out Micro SD card memory , 128 GB, IP67, IK10, PoE Smart Detection (Tripwire Intrusion Scene Change Object Abandoned/Missing Face)</p>		53,000,000
35 HDW4831EMP-ASE	<p>1/2.5" 4K progressive scan CMOS H.265+/H.265/H.264+/H.264 encoding 15fps@4K(3840×2160), 25/30fps@3Mp(2304×1296) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 4mm fixed lens, Max. IR LEDs Length 50m Built-in Mic , Micro SD card memory , 128 GB IP67, PoE, (Tripwire Intrusion Scene Change Object Abandoned/Missing Face)</p>		53,000,000
36 HDW4631EM-ASE Eco-Savvy Lite	<p>1/2.9" 6Megapixel progressive scan STARVISTM CMOS H. 265+ & H.265 & H.264+ & H.264 triple-stream encoding 20fps@6MP(3072×2048), 25/30fps@4MP(2688×1520) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 2.8mm fixed lens, Built-in Mic Max. IR LEDs Length 50m, Smart IR Micro SD card memory , 128 GB, IP67, PoE (Tripwire Intrusion Object Abandoned/Missing Face)</p>		44,000,000
37 HDW4431EMP-AS-S4	<p>4MP IR Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 2.8mm fixed lens 25/30fps@4Mp(2688×1520) H.265&H.264 triple-stream encoding IVS(Tripwire, Intrusion, Object Abandoned/Missing, Face detection) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE</p>		32,200,000
39 HDBW2531RP-ZAS	<p>1/2.7" 5Megapixel progressive CMOS 2.7~13.5mm Motorized lens 20fps@5M(2592×1944)&25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC 1/1 Audio in/out, 1/1 Alarm in/out Micro SD card 128GB Max IR LEDs Length 30m ,Smart IR IP67, IK10, PoE</p>		50,000,000

40	HDW3441TMP-AS-0280B Starlight Wiz Sense	4MP IR Fixed focal Eyeball WizSense Network Camera 1/3" 4Megapixel progressive CMOS Min. Illumination:0.005 Lux@F1.6 2.8mm Motorized lens 25/30fps@4Mp(2688×1520) SMART H.264+/H.265+ triple-stream encoding IVS(Tripwire; intrusion (Recognition of human and vehicle)) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic Micro SD memory 256GB Max. IR LEDs Length 50m, Smart IR, IP67, PoE		34,000,000
41	HDBW2431RP-ZAS-S2 Starlight	4MP WDR IR Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.5 2.7–13.5 mm Motorized lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic 1/1 Audio in/out, 1/1 Alarm in/out max IR distance:40 m, Smart IR IP67, IK10, PoE		45,000,000
42	HDBW2431EP-S-S2 Starlight	4MP IR Mini Dome Network Camera 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux @ F1.6 3.6 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB max IR distance:30 m, Smart IR IP67, IK10, PoE		25,200,000
43	HDW2431TMP-AS-S2 Starlight	4MP WDR IR Eyeball Network Camera, Starlight 1/3" 4Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding 4MP (2688 × 1520)@20 fps,2560 × 1440 @25fps Min. Illumination:0.008 Lux@F1.6 2.8 mm Fixed lens WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Smart Detection (Tripwire Intrusion) Micro SD memory 256 GB, Built in Mic max IR distance:30 m, Smart IR IP67, PoE		26,200,000
44	HDW1431T1P-0280B-S4	4MP Entry IR Fixed-focal Eyeball Network Camera 1/3" 4Megapixel progressive CMOS 20fps@4.1M(2688×1520) & 25fps@4M(2560×1440) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC Support ROI Max. IR LEDs Length 30m, IP67, PoE		20,500,000
45	HDBW1431EP Ambarella	1/3" 4Megapixel progressive CMOS, 3.6mm fixed lens 20fps@4M(2688×1520) & 25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE		28,000,000

مدل ردیف	مشخصات فنی	تصویر	قیمت (ریال)
46 HDW1431SP 	1/3" 4Megapixel progressive CMOS, 2.8mm fixed lens 20fps@4M(2688×1520) &25/30fps@3M(2304×1296) H.265+/H.265/H.264+/H.264 dual-stream encoding WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, PoE		27,500,000
47 HDW2231TMP-AS-S2 	2MP WDR IR Eyeball Network Camera, Starlight 1/2.8" 2Megapixel progressive CMOS Min. Illumination:0.002 Lux@F1.6 Outputs max. 2MP (1920 × 1080) @25/30 fps 2.8mm Fixed lens SMART H.264/H.265 dual-stream encoding IVS(Tripwire, intrusion) WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI Built-in Mic, Micro SD memory 256GB Max. IR LEDs Length 30m, Smart IR, IP67, PoE		23,800,000
48 HDW1230T1P-S4	2MP Entry IR Fixed-Focal Eyeball Network Camera 1/2.7" 2Megapixel progressive CMOS SMART H.264/H.265 dual stream encoding max. 2MP (1920 × 1080P) @25/30 fps Min. Illumination:0.01 Lux@F2.0 2.8 Fixed lens DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC, HLC, ROI, EIS max IR distance:30 m, Smart IR IP67, PoE		16,300,000
49 HDW1230SP	1/2.7" 2Megapixel progressive scan CMOS, 2.8mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, PoE		18,000,000
50 HDBW1230EP	1/2.7" 2Megapixel progressive scan CMOS, 3.6mm fixed lens H.265+/H.265/H.264+/H.264 dual-stream encoding 25/30fps@1080P(1920×1080) DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC Max. IR LEDs Length 30m, IP67, IK10, PoE		18,400,000
51 DH-SD29204T-GN	1/2.7" 2MP CMOS Sensor, 2.7mm ~ 11mm , 4x Optical Zoom H.264+/H.264 Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max 100°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Built-in Mic, IR Distance up to 30m, POE, (Tripwire Intrusion Scene Change Face Abandoned-Missing Object)		49,700,000
52 DH-SD1A203T-GN	1/2.8" 2MP STARVIS™ CMOS (Starlight) H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 25/30fps@1080P, 2.7mm ~ 8.1mm , 3x Optical Zoom WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Max Pan: 80° /s; Tilt: 40° /s speed Pan: 0° ~ 355°; Tilt: 5° ~ 90° rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern, Support Defog, IR Distance up to 15m, IP 66, support POE (Tripwire Intrusion Abandoned/Missing Face Detection)		53,000,000

<p>53 DH-SD6CE230U-HNI</p>	<p>1/2.8" 2MP STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P 4.5mm~135mm Powerful 30x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map), Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Alarm 7/2 in/out, Audio 1/1 in/out, 1*Video output RS485, IR Distance up to 200m, PoE+, IP67, IK10</p>		<p>237,000,000</p>
<p>54 SD6CE225U-HNI</p>	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Max. 50/60fps@1080P, 4.8mm~120mm 25x optical zoom Max 200°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC Support Defog, ROI, EIS, Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 Alarm 7/2 in/out, Audio 1/1 in/out IR Distance up to 200m, PoE+, IP67, IK10</p>		<p>158,000,000</p>
<p>55 DH-SD6CE245U-HNI</p> <p>Starlight</p>	<p>2MP 45x Starlight IR PTZ Network Camera 1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6), B/W(0.0005Lux@F1.6) Max. 50/60fps@1080P, 3.95mm~177.7mm Focal Length 45x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR, BLC, HLC, AGC, AWB Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Heat Map) Support Defog, ROI, EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 1*Video output, Rs485 7/2 Alarm in/out, 1/1 Audio in/out IR Distance up to 250m, PoE+, IP67, IK10</p>		<p>Call</p>
<p>56 SD49225XA-HNR</p>	<p>2MP 25x Starlight IR PTZ AI Network Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264/MJPEG (sub stream) Max. 1~60fps@1080P,960P, 720P 4.8mm~120mm 25x optical zoom Max 240°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR)(Color/B/W), Ultra DNR(2D/3D), BLC, HLC, AWB, AGC, Auto iris, Auto focus IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection, Human, Vehicle, SMD Plus, Region of Interest) False Alarm Avoidance for Animals, Leaves, Bright Light Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out, Support PoE+</p>		<p>133,000,000</p>
<p>57 SD49225T-HN-S2</p> <p>Starlight</p>	<p>1/2.8" 2Megapixel STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Triple-streams encoding Minimum Illumination:Color(0.005Lux@F1.6)B/W:(0.0005Lux@F1.6) Max. 25/30fps@1080P, 4.8mm~120mm 25x optical zoom WDR(120dB), Day/Night(ICR), Ultra DNR,BLC, HLC, AWB, AGC, ROI Support Defog IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 2/1 Alarm in/out, 1/1 Audio in/out Support PoE+, IR Distance up to 100m, IP66</p>		<p>122,000,000</p>

<p>58 SD65F230F-HNI</p> <p>Super Starlight</p>	<p>1/1.9" 2MP CMOS Sensor(Super Starlight) H.264 / MJPEG Encoding Max. 25/30fps@1080P, 25/30/50/60fps@720P 6mm~180mm Powerful 30x optical zoom Max 300°/s pan speed, 360° endless pan rotation WDR(120db), Day/Night(ICR), Ultra DNR, BLC, HLC, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection) Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Support Defog, ROI, EIS Alarm 7/2 in/out, Audio 1/1 in/out, 1 video output RS485, IR Distance up to 100m, Support PoE+, IP66,IK10</p>		<p>Call</p>
<p>59 DH-SD59432XA-HNR</p> <p>Starlight Wiz Sense</p>	<p>4MP 32x Starlight IR WizSense Network PTZ Camera 1/2.8" STARVIS™ CMOS H.265+/H.265/H.264+/H.264 Encoding Min. Illumination:Color(0.005Lux@F1.3)B/W(0.0005Lux@F1.3) Max. 25/30fps@4M 4.9 mm–156 mm Focal Length, 32x optical zoom Deep-learning-based auto tracking and perimeter protection(Recognition of human and vehicle) IVS(Tripwire, intrusion, Object abandoned/missing, Face Detection) WDR(120dB), Day/Night(ICR), Ultra DNR, AWB, AGC, BLC, HLC Support Defog and EIS , Rol Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66</p>		<p>295,000,000</p>
<p>60 SD59225U-HNI</p>	<p>2MP 25x Starlight IR PTZ Network Camera 1/2.8" Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.8mm~120mm 25x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+, IR Distance up to 150m, IP66,OSD</p>		<p>148,000,000</p>
<p>61 SD59230U-HNI</p> <p>Starlight</p>	<p>2MP 30x Starlight IR PTZ Network Camera 1/2.8" Exmor R CMOS H.265+/H.265/H.264+/H.264 Encoding Max. 50/60fps@1080P, 25/30/50/60fps@720P 4.5mm~135mm 30x optical zoom Max 400°/s pan speed, 360° endless pan rotation WDR(120dB), Day/Night(ICR), Ultra DNR, Auto iris, Auto focus Auto-tracking and IVS(Tripwire, Intrusion,Abandoned/Missing, Face Detection), Support Defog and EIS Up to 300 presets,8 tour, 5 pattern, Auto scan, Auto Pan Built-in 2/1 Alarm in/out, Audio 1/1 in/out Support PoE+. IR Distance up to 150m. IP66.OSD</p>		<p>220,000,000</p>
<p>62 SD59430U-HNI</p>	<p>1/3" CMOS Sensor H.265+/H.265/H.264+/H.264 Encoding, Ultra-low bit rate Max. 25/30fps@4M(2592×1520) & 50/60fps @1080P resolution WDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 400°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out, IP66, POE+ IR Distance up to 100m(AC24V)/ 80m(DC12V) Smart Detection (Tripwire Intrusion Scene Change Face Anonedned-Missing Object)</p>		<p>248,000,000</p>

63	SD60230T-HN	<p>1/2.8" 2Mp CMOS Sensor H.264+/H.264 Encoding, Ultra-low bit rate transmission Max. 30fps@1080P(2592×1520) & 60fps @720P resolution DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus 4.5mm ~ 135.0mm , 30x Optical Zoom Max 600°/s pan speed, 360° endless pan rotation Up to 300 presets, 5 auto scan, 8 tour, 5 pattern Micro SD card memory , 64 GB Audio In/Out, Alarm In/Out IP67,IK10, POE+, (Tripwire Intrusion Scene Change Face Anandoned-Missing Object)</p>		Call
64	NVR2104HS-4KS2	<p>4 channel IP camera input H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		20,200,000
65	NVR2104HS-P-4KS2	<p>4 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 4PoE Port, P2P support</p>		29,000,000
66	NVR2108HS-4KS2	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		22,800,000
67	NVR2108HS-8P-4KS2	<p>8 channel IP camera input, H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8Mp resolution preview&playback Up to 1ch@8MP/4ch@1080P decoding HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, 8Port PoE, P2P support</p>		39,000,000
68	NVR4108HS-4KS2	<p>8 channel IP camera input 1/4/8/9 channel Live Preview, 8CH Playback H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		26,500,000
69	NVR4116HS-4KS2	<p>16 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 1 SATA HDD up to 6TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		38,500,000
	NVR4116HS-4KS2/L	<p>16 channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec decoding Max 80Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 16-ch@720P decoding capacity Support SMD Plus by Camera HDMI(4K)/VGA simultaneous video output Support 1 SATA HDD up to 8TB, 2 USB2.0 100 Mbps Network Card, P2P support</p>		37,500,000

NEW Product

<p>70 NVR4216-4KS2</p>	<p>16 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card, P2P support</p>	 <p>54,000,000</p>
<p>NVR4216-4KS2/L NEW Product</p>	<p>16 channel IP camera input, 16 channel Live Preview Smart H.265/H.264 codec decoding Max128Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback 8-ch@1080P decoding capability HDMI(4K)/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card, P2P support</p>	 <p>50,000,000</p>
<p>71 NVR4232-4KS2</p>	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 2 SATA HDD up to 6TB 2 USB Ports (1 USB2.0, 1 USB3.0) 4 Alarm Input, 2 Relay Output 1*10/100/1000Mbps Mbps Network Card, P2P support</p>	 <p>59,000,000</p>
<p>72 DHI-NVR5232-4KS2(V2.0)</p>	<p>32Channel 1U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 1*HDMI(4K)/1*VGA simultaneous video output 2*SATA HDDs(10 TB for each HDD), 2 USB(1 USB3.0,1 USB2.0) 1*1000 Mbps Network Card RS232, RS485,4/2 Alarm In/out , P2P Support</p>	 <p>94,500,000</p>
<p>73 NVR4432-4KS2</p>	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 4 SATA HDD up to 6TB, 2 USB Ports (1 USB2 & 1 USB3) 16 Alarm Input, 4 Relay Output, RS232 , RS485 2*10/100/1000Mbps Mbps Network Card, P2P support</p>	 <p>84,500,000</p>
<p>74 NVR5432-4KS2(V2.0)</p>	<p>32Channel 1.5U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support</p>	 <p>145,000,000</p>
<p>75 DHI-NVR5464-4KS2(V2.0)</p>	<p>64Channel 1.5U 4K&H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 4*SATA HDDs(10 TB for each HDD), 3 USB(2 USB3.0,1 USB2.0) Support 1 e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support</p>	 <p>169,000,000</p>

76	NVR4832-4KS2	<p>32 channel IP camera input, 16 channel Live Preview H.265/H.264 codec decoding Max 200Mbps incoming bandwidth Up to 8MP Resolution for Preview and Playback HDMI/VGA simultaneous video output Support 8 SATA HDD up to 6TB 3 USB Ports (2 USB2.0, 1 USB3.0) 16 Alarm Input, 4 Relay Output, RS232 , RS485 2*10/100/1000Mbps Mbps Network Card, P2P support</p>		139,000,000
77	NVR5832-4KS2	<p>32 channel IPC input, 32 Channel Live Preview H.265/H.264/MJPEG/MPEG4 codec decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview&playback Max 16ch@1080P 4ch@4K H.265 H.264 Playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 16 Alarm In , 6 Relay Output, P2P Support, Raid 0/1/5/6/10</p>		200,000,000
78	DHI-NVR5864-4KS2(V2.0)	<p>64 Channel 2U 4K & H.265 Pro Network Video Recorder (V2.00) Smart H.265+/H.265/H.264+/H.264/MJPEG decoding Max 320Mbps incoming bandwidth Up to 12Mp resolution preview & playback Max 4-ch@8MP(30fps), 16-ch@1080P(30fps) decoding 2*HDMI/2*VGA simultaneous video output 8*SATA HDDs(10 TB for each HDD), 4 USB(2 USB3.0,2 USB2.0) 1*e-SATA, 2*1000 Mbps Network Card RS232, RS485,16/6 Alarm In/out , P2P Support</p>		250,000,000
79	NVR608-32-4KS2	<p>Intel Dual-core Processor, 32 channel IPC input, 32 Channel Live Preview (1st Screen:1/4/8/9/16/25/36,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding, Max 384Mbps incoming bandwidth Up to 12Mp resolution preview&playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10, 4 USB(2 USB3.0, 2 USB2.0) 2*1000 Mbps Network Card, RS232 , RS485, 16 Alarm In , 8 Relay Output</p>		213,000,000
80	NVR608-64-4KS2	<p>Intel Quad-core Processor 64 channel IPC input, 32 Channel Live Preview (1st Screen:1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16), H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI/VGA simultaneous video output Support 8 SATA HDDs up to 48TB,1 eSATA Port Support Raid 0/1/5/6/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16 Alarm In , 8 Relay Output</p>		360,000,000
81	DHI-NVR608-128-4KS2	<p>128 Channel 2U Ultra 4K H.265 Network Video Recorder (1st Screen: 1/4/8/9/16/25/36 ,2nd Screen: 1/4/8/9/16) H.265/H.264/MJPEG codec decoding Max 384Mbps incoming bandwidth Up to 12Mp resolution preview & playback 2HDMI(different Source)/VGA simultaneous video output Support 8 SATA (8TB for each HDD),1 eSATA Port Support Raid 0/1/5/10 Support Smart Tracking and Intelligent Video 4 USB(2 USB3.0, 2 USB2.0), 2*1000 Mbps Network Card RS232 , RS485, 16/8 Alarm In/Output</p>		470,000,000

<p>82 ESS1508C</p>	<p>2U standard 19-inch rack case Connect master device via eSATA or USB 1 eSATA port transmission speed up to 3Gbps 1 USB 3.0 port data transmission higher than normal Powerful R / W performance: read >64MB/s, write >64MB/s ESS1508C: Max support Internal 8 SATA HDD up to 48TB Recommended with DVR, NVR connection</p>		<p>78,000,000</p>
<p>83 PFS3006-4ET-60</p>	<p>4-Port Fast Ethernet PoE Switch, Layer two commercial switch 2*10/100 Mbps Uplink ports, 4*10/100 Mbps PoE ports Port1≤60W, Port2-4≤30W, Totals≤60W Support IEEE802.3af, IEEE802.3at(PoE+), Hi PoE 1.8Gbps Switching Capacity 890Kpps Mpps Packet Forwarding Rate 768Kb Packet Buffer Memory MAC atable size is 2K, Supports DC 48-57V power supply</p>		<p>11,700,000</p>
<p>84 PFS3010-8ET-96</p>	<p>8-Port Fast Ethernet PoE Switch, Layer two commercial switch 2*10/100/1000 Mbps Ports, 8*10/100 Mbps PoE Ports Port1≤60W, Port2-8≤30W, Totals≤96W Support IEEE802.3af (PoE), IEEE802.3at (PoE+), Hi-PoE 5.6Gbps Switching Capacity, 4.17 MppsPacket Forwarding Rate 4Mb Packet Buffer Memory MAC Table Size is 16K, Supports DC 48-57V power supply</p>		<p>21,400,000</p>
<p>85 PFS3110-8P-96</p>	<p>Two-layer industrial PoE switch 1*1000 Base-X, 1*10/100/1000 Base-T 8*10/100 Base-T (PoE power supply) Each POE power ≤30W, Total≤96W Support IEEE802.3af, IEEE802.3at standard 7.6G Switching Capacity, 4.17 MppsPacket Forwarding Rate 1Mb Packet Buffer Memory, Industrial wide temperature design MAC auto study and aging, MAC address list capacity is 8K</p>		<p>26,700,000</p>
<p>86 PFS4218-16ET-190</p>	<p>Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Totals≤190W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity,5.36 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		<p>67,500,000</p>
<p>87 PFS4218-16ET-240</p>	<p>Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 16*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Totals≤240W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 5.36 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		<p>73,000,000</p>
<p>88 PFS4226-24ET-240</p>	<p>24-Port PoE Switch, Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Totals≤240W Support IEEE802.3af, IEEE802.3at, Hi-PoE 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate Network Management by WEB(http and https protocol)</p>		<p>80,600,000</p>

89	PFS4226-24ET-360	<p>24-Port PoE Switch, Layer 2 management PoE switch 2*10/100/1000 Base-T (Combo port) 2*1000 Base-X (Combo port) 24*10/100 Base-T (PoE power supply) Port1/2 support Hi-PoE (60W), PoE+, PoE Each power ≤30W, Total≤360W, Support PoE, PoE+, Hi-PoE 'Orange port' support Hi-PoE, can be used with the PoE extender (PFT1300) 250 meters long distance PoE transmission Support spanning tree protocol STP/RSTP Support Vlan:VLAN/802.1Q Standard Vlan 8.8G Switching Capacity, 6.55 Mpps Packet Forwarding Rate Support Web management, Non-blocking video transmission management, PoE Setting/Event Statistics/Green PoE</p>		96,700,000
90	PFS4226-24GT-360	<p>24-Port PoE Gigabit Managed Switch Layer 2 network management PoE switch 24*10/100/1000 Base-T (PoE power supply) 2*100/1000 Base-X, Port1/2 support Hi-PoE (60W) Each power ≤30W, PoE Budget≤360W Spanning tree: STP/RSTP/MSTP Network management based on SNMP Configuration: Web, Telnet, CLI Command Support Vlan:VLAN/802.1Q Standard Vlan, 8K MAC Table 52G Switching Capacity, 38.688 Mpps Packet Forwarding Rate EMC high protection design</p>		123,000,000
91	PFT1300	<p>PoE Extender 1*10/100 Base-T PoE power receiving port 1*10/100 Base-T PoE power supply port, supply power for the next extender 1*10/100 Base-T PoE power supply port, supply power for IPC Support passive PoE cascade power supply and Ethernet data exchange Support IEEE 802.3af/at standard power supply IP Camera able to cascade level 2 PoE Extender, connect to 3 IPC (power consumption ≤8W), maxtransmission distance 300m</p>		5,150,000
92	PFM700	<p>*1 Channel HDMI Transmission Signal *1080P/1080I/720P/576P/576I/480P/480I Resolution Output Signal , *60M (max)Transmission Distance *Input voltage DC5V *Use single UTP (CAT-5E and CAT-6) real-time transmit 1-ch HD video, signal:support HDMI 1.3</p>		14,400,000
93	NKB1000	<p>Keyboard to Control : Dahua High Speed Dome (all models) Dahua Standalone DVR , Dahua Network High Speed Dome Network Video Server Connection : RS485, RS422, USB, RS232 & Network Three Dimensional Joystick Control of PTZ Functions Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control, On-Screen Menu & User Operation Procedure Tips Connect to SmartPSS via USB</p>		71,000,000